



Material Safety Data Sheet
 Golden West Premium Universal
 Tractor Fluid - J20C

Material Safety Data Sheet May be used to comply with OSHA's Hazard Communication Standard, 39 CFR 1910.1200. Standard must be 39 CFR 1910.1200. Standard must be consulted for specific requirements.		U.S. Department of Labor Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072	
Identity (As Used on Label and List) Golden West Premium Universal Tractor Fluid - J20C		Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.	
Section I			
Manufacturer's Name Golden West Packaging Plant		Emergency Telephone Number 210-649-1401	
Address (Number, street, city, state and ZIP code) 13598 Hwy 87 East Adkins, TX 78101		Telephone Number for Information 210-649-1401	
		Date Prepared 2008	
		Signature of Preparer (optional)	
Section II - Hazardous Ingredients/Identity Information			
Petroleum Hydrocarbon with Additives		NEPA Health - 1 Flammability - 1 Reactivity - 0	
Section III - Physical/Chemical Characteristics			
Boiling Point	800°F	Specific Gravity (H2O = 1)	0.0835
Vapor Pressure (mm Hg.)	<1	Melting Point	N.A.
Vapor Density (AIR = 1)	1+	Evaporation Rate (Butyl Acetate = 1)	<1
Solubility in Water - Negligible			
Appearance and Odor - light to dark amber, hydrocarbon odor			
Section IV - Fire and Explosion Hazard Data			
Flash Point (Method Used)	392°F	Flammable Limits No Data	LEL N.A. UEL N.A.
Extinguishing Media - Use Dry Chemical, Foam or Carbon Dioxide.			
Special Fire Fighting Procedures - Water may be used to cool down containers exposed to flame.			
Unusual Fire Explosion Hazards - Dense smoke could contain Carbon Monoxide			
Style CU-FP 174 Labelmaster, Div. Of American Labelmark Co. Inc. 60646		OSHA 174, Sept. 1985	

Section V - Reactivity Data				
Stability - Stable		Conditions to Avoid - High heat. Exposure to flame.		
Incompatibility (Materials to Avoid) - None				
Hazardous Decomposition or Byproducts - Burning could result in release of Carbon Monoxide fumes.				
Hazardous Polymerization	May Occur	Conditions to Avoid -		
	Will Not Occur - x			
Section VI - Health Hazard Data				
Route(s) of Entry: Eyes, Mouth, Skin		Inhalation? Yes	Skin? Yes	Ingestion? Possible - Yes
Health Hazards (Acute and Chronic) - Prolonged contact with skin could cause irritation.				
Carcinogenicity: N.A.	NTP?	IARC Monographs?	OSHA Regulated?	
Signs and Symptoms of Exposure - Redness of skin after exposure.				
Medical Conditions Generally Aggravated - Asthma when inhaled.				
Emergency First Aid Procedures - Wash effected area with soap and water.				
Section VII - Precautions for Safe Handling and Use				
Steps to be Taken in Case Material is Released or Spilled - Use absorbent material to clean up. Contain spilled product in area spilled. Dispose of properly.				
Waste Disposal Method - As directed by state guidelines.				
Precautions to be Taken in Handling and Storing - Store in cool - dry place. Avoid spills.				
Other Precautions - Keep containers away from sparks and flame.				
Section VII - Control Measures				
Respiratory Protection (Specify Type) - Required				
Ventilation -	Local Exhaust - x	Special -		
	Mechanical (General) - x	Other -		
Protective Gloves - Recommended				
Eye Protection - Recommended				
Other Protective Clothing or Equipment - N.A.				
Work/Hygienic Practices - Clean spilled product immediately.				
U.S.G. P.O.: 1986-491-529/45775				